



Armored Mercedes-Benz 5500

ALPINE ARMORING INC.

alpineco.com

Table of Contents	Page 2
Vehicle Specifications	Page 3
Opaque Armor Details	Page 4
Transparent Armor Details	Page 5
Additional Features	Page 6
Completed Vehicle Photos	Page 7-8
Ballistic Reference Chart	Page 9
Vehicle Warranty	Page 10

GENERAL SPECIFICATIONS

VIN: WDD2221821A255015

MAKE: Mercedes Benz

MODEL: S500

YEAR: 2016

ENGINE: 4.7L V8 Gasoline

POWER: **449** hp @ 5,200 rpm

TRANSMISSION: 7-Speed Auto w/Shift Paddles

COLOR: Black

INTERIOR: Grey/Seashell Leather

SEATING: 2 + 3

6,800 lbs. (3,084 kg) **APPROX. WEIGHT:**

OTHER SPECIFICATIONS

HEIGHT:

59 in.

(149 cm)

WIDTH:

84 in.

(212 cm)

LENGTH:

206.5 in.

(524 cm)

WHEELBASE:

124.6 in.

(316 cm)





Firewall

Ballistic steel lines the firewall and provides protection up front.

4-1



Roof is lined with ballistic steel at angle.





Floor

Floor is lined with ballistic steel to protect against mines and grenade blasts.

4-3

Doors

All doors are lined with ballistic steel.





Battery Protection

Entire battery is enclosed in a fully ballistic steel casing.

4-5

Heavy-Duty Door Straps

Custom heavy duty door straps that will withstand the weight of the armored doors.





Overlaps

All doors and windows feature ballistic steel overlaps to keep shrapnel from angle shots from entering the cabin.

4-7


Wheel Wells

Front and rear wheel wells are lined with ballistic steel.










s image is property of Alpine Armorin

Glass Thickness

Minimum up to 39 mm thick glass/polycarbonate composite transparent armor.

5-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area.

5-2



Multi-Hit Protection

All windows are capable of sustaining multiple hits while providing protection to passengers.

5-3



Anchored Windows

All windows are anchored for additional protection from explosions.









P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

6-1

Emergency Lighting

White LED lights are mounted in the front grill and visor area.





Power Windows

The front two windows are powered and lower approximately 5-6 inches for documents pass-thru.

6-2

Battery Protection

The battery is encased in a ballistic steel box.





ECM Protection

Electronic control module is encased in a ballistic steel box.

6-3

Fuel Tank Protection

The fuel tank is encased in a ballistic steel box to protect against mines and grenades.





Special Door Overlaps

All doors and windows feature built in ballistic steel overlaps.

6-4

Undercarriage Protection

Ballistic steel to protect all undercarriage of vehicle.





* Tel:+1.703.471.0002 * Fax:+1.703.471.0202 * www.alpineco.com * sales@alpineco.com *



















































A										"no one protects you better"		
WEAPONS	SPECS			LEVELS				BULLETS			NUMBER OF SHOTS	
4	ТҮРЕ	CALIBER (mm)	CLASS	STANAG	UL	ALPINE	NIJ	CEN	MASS (g)	MATERIAL	VELOCITY	NUMBER OF SHUTS
	.38 Special	9 x 19	Handgun	-	1	A1	I.II.IIA	-	8.00	rca	358 M/S	
	.357 Magnum	9 x 33	Handgun	-	2	A2	I.IIA	B1 & B3	10.20	JSP	430 M/S	
	.44 Magnum	11 x 33	Handgun	-	3	АЗ	IIIA	B4	15.60	LWC	440 M/S	
1	MP5	9 x 19	SMG	-	6	A4	IIIA	B2	8.00	ľCO	427 M/S	5 ===
	Shotgun	12 Gauge	Shotgun	-	3 & 4	Aã	IIIA	SG2	28.30	SLUG	503 M/S	3
	Tokarev	7.62 x 25	Handgun	-	-	A5	IIIA	-	5.50	LCSJ	488 M/S	-i
	Kalashnikov (AK-47)	7.62 x 39	Assault Rifle	-	-	A6	III	B5	9.70	SCCI	732 M/s	
-	Kalashnikov (AK-47 Military)	7.62 x 39 API BZ	Assault Rifle	II	_	A7	_	B5+	11.70	2CC1	774 M/s	
PATH	M16/AR-15	5.56 x 45 NATO SS109 5.56 x 45 NATO Ball	Assault Rifle	1	7	A8	IV	B5	4.00	rcci 2cci	900 M/s 833 M/s	3
-	Winchester .308	7.62 x 51	Rifle	1	7	A9	III	B6	10.90	rcci	810 M/s	5
	Remington 700 SPS	742 × 63 AP (.30-06)	High-Power Rifle	III	5 & 8	A10	IV	B7-	10.80 8.40	AP	869 M/s 930 M/s	5
	Dragunov	7.62 x 54R B32 API	Sniper Rifle	111	-	A11	IV+	B7+	10.04	2CC1	854 M/S	
	50 Cal	12.7 x 99	High-Power Rifle	IV	10	A12	-	-	45.00	CJ	908 M/s	



UL Underwriters Laboratory, 752

NIJ National Institute of Justice, 0108.01

CEN European Standard

STANAG ... NATO's Standard (STANAG 4569)

ALPINE Alpine Armoring's Certified Standard

LCCJ Lead Core Copper Jacket JSP Jacketed Soft Point

LWC Lead Wad Cutter

LCSJ Lead Core Steel Jacket SCCJ Steel Core Copper Jacket

AP Armor Piercing

SG Shotgun

Shots (5) 11.4 cm Square Pattern (Corners & Center)

Shots (3) 11.4 cm Triangular Pattern

Velocity Minimum Measured Velocity

NIJ Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required calibers of ballistic threat)













