

Armored Mercedes-Benz GL550

ALPINE ARMORING INC.

alpineco.com



Table of Content	Page 2
Vehicle Specifications	Page 3
Opaque Armor Details	Page 4
Transparent Armor Details	Page 5
Additional Features	Page 6
Completed Vehicle Photos	Page 7
Ballistic Reference Chart	Page 8
Vehicle Warranty	Page 9

MERCEDES-BENZ GL550

VIN: 4JGDF7DE4EA302130

GENERAL SPECIFICATIONS

VIN: 4JGDF7DE4EA302130

MAKE: Mercedes-Benz

MODEL: GL550 4MATIC

YEAR: 2014

ENGINE: 4.7L Bi-turbo V8 Gasoline

429 hp @ 5,250 rpm POWER:

TRANSMISSION: 7-Speed Automatic

COLOR: Black

INTERIOR: Black leather

SEATING: 2 + 3 + 2

FINAL WEIGHT: 7,840 lbs. (3,556 kg)

DIMENSIONS

HEIGHT:

73 in.

(185 cm)

WIDTH:

84 in.

(213 cm)

LENGTH:


202 in.

(513 cm)

WHEELBASE:

121 in.

(307 cm)





Firewall

Ballistic steel firewall provides protection up front.

5-1



Roof is lined with ballistic steel at an angle.





Floor

Entire floor is lined with ballistic steel.

5-2

Doors

All doors are lined with ballistic steel.





Window Anchors

All windows are mounted to ballistic steel anchors to provide more protection during a blast.

5-3

Overlaps

All doors and windows feature ballistic steel overlaps to protect against angle shots.





Heavy-Duty Hinges

Custom hinges that will withstand the weight of the armored doors.

Wheel Wells

Front and rear wheel wells are lined with ballistic steel.







LPINE ARMORING IN



Glass Thickness

Minimum 40 mm thick glass/polycarbonate composite transparent armor.

7-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area.

7-2



Multi-Hit Protection

All windows are capable of sustaining multiple hits while providing protection to passengers.

7-3



Anchored Windows

All windows are anchored for additional protection from explosions.

7-4





ADDITIONAL FEATURES

P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

8-1

Rear Door Partition

A separate ballistic steel rear door and partition are built in, making it so the tailgate doesn't need to be armored.

8-5





Power Windows

The front two windows are powered and lower approximately 5-6 inches.

8-2

Strobe Lights

A pair of red/blue strobe lights are mounted in the front grill area.





Intercom System

An intercom system is installed on the vehicle, allowing 2-way communication between the driver and people outside.

8-3

Safety Bands

All wheels, including the spare are equipped with safety bands.





Fuel Tank Protection

The fuel tank is encased in a ballistic steel box to protect against mines and grenades.

Exhaust Protection

The exhaust is protected by a steel mesh to prevent sabotage.







PINE ARMORING INC

























ALPINE ARMORING'S BALLISTIC CHART

(3)	SPECS			LEVELS			BULLETS			"no one protects you better"		
WEAPONS	TYPE	CALIBER (ma)	CLASS	STANAG	UL	ALPINE	NU	CEN	MASS (II)	MATERIAL	VELOCITY	NUMBER OF SHOTS
-	38 Special	9 x 19	Hendgen	-	1	A1	LILIA		8.00	ttti	358 4/5	-
	357 Magnum	9 x 33	Hendgun	-	2	A2	LIIA	81 a. 83	10.20	158	430 W/S	, —
	.44 Magners	11 x 33	Handgun	12	3	АЗ	IIA	84	15.60	LWC	440 H/5	. —
77	MP5	9 x 19	SMS	35	6	A4	IIIA	82	8.00	ICO	# 427 H/S	. —
-	Shotgan	12 Gouge	Shotgun	1	384	Aŝ	IIIA	562	28.30	Stug	503 W/S	
Brand .	Tokorev	7.62 x 25	Handgun		-	A5	IIIA	-	5.50	ter	488 M/S	
-	Koloshnikov (M47)	7.62 x 39	Asseult Rifle	-	-	A6		85	9.70	SCO	732 W/S	
-	Kalesheikov (M. 47 Milesy)	7.62 x 39 API EZ	Assoult Rifle	11	170	A7	25-0	85+	11.70	5001	774 N/S	
PER STATE OF	M16/AR-15	5.56 x 45 MXT0 50009 5.56 x 45 MXT0 Bell	Asseult Rifle	1	7	A8	W	85	4.00	SCC1 LCC1	900 M/S = 833 M/S	
	Windnester 308	7.62 x 51	Rifle	1	1	A9	211	85	10.90	w	810 H/S	5
Married .	Euroington 7/00 SPS	747×45 計[30-86]	High-Power Rifle	111	548	A10	W	87-	10.80 8.40	NF.	869 M/S 930 M/S	5
	Distinga	7.62 x 54R 832 NPI	Sniper Rifle	11	-	A11	N+	87+	10.04	SCO.	854 M/s	
		12.7 x 99	High Fower Rifle	N	10	A12	-	-	45.00	CI.		
-75	50 Cel	12.7 x 99	night cover fulle	N	10	A12		-	45.00	C)	908 M/S	



Underwriters Laboratory, 752

National Institute of Justice, 0108.01

European Standard

... NATO's Standard (STANAG 4569)

... Alpine Armoring's Certified Standard

Lead Care Copper Jacket Jacketed Soft Point Lead Wad Cutter LCC1 ISP

LWC

Lead Core Steel Jacket LCSJ Steel Core Copper Jacket SCCI

AP Armor Piercing

56. Shotgun Shots (5) 11.4 cm Square Pattern (Corners & Center)

Shots (3) 11.4 cm Triangular Pattern

Minimum Measured Velocity

NIJ Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required colibers of ballistic threat)











